

## BRAVO ELECTRICAL WATER HEATERS SMALL LITRE CAPACITY

ERP



- Range of 5 models with 10, 15 and 30 litre capacities
- 10 and 15-litre models available in versions for installation over and under the sink

### > EQUIPPED WITH:

- Stainless steel electrical heating elements
- Glass-porcelain storage tank
- High concentration magnesium anode
- External temperature regulator
- Plastic external casing
- Capillary temperature-control thermostat

\* UNDER SINK

| MODEL             |               | SN 10    | SN 10 S* | SN 15    | SN 15 S* | SN 30    |
|-------------------|---------------|----------|----------|----------|----------|----------|
| Load profile      |               | XXS      | XXS      | XXS      | XXS      | S        |
| ERP Class         | (Class G - A) | <b>B</b> | <b>B</b> | <b>B</b> | <b>B</b> | <b>C</b> |
| Tank capacity     | l             | 10       | 10       | 15       | 15       | 30       |
| Electrical power  | W             | 1500     | 1500     | 1500     | 1500     | 1500     |
| Heating time      | 20+55°C       | 24min    | 25min    | 35min    | 35min    | 68min    |
| Protection rating | IP            | 24       | 24       | 24       | 24       | 24       |
| Empty weight      | Kg            | 6.5      | 6.5      | 7.8      | 7.8      | 11.5     |

## NOVO ELECTRICAL WATER HEATERS SMALL LITRE CAPACITY

ERP



- Range composed of 2 models with 5 and 10-litre capacity both available in versions over and under-sink

### > EQUIPPED WITH:

- Stainless steel electrical heating elements
- Glass-porcelain storage tank
- High concentration magnesium anode
- External temperature regulator with LED reporting when the set-point is reached
- Capillary temperature-control thermostat

\* UNDER SINK

| MODEL            |               | 5        | 5 S*     | 10       | 10 S*    |
|------------------|---------------|----------|----------|----------|----------|
| Load profile     |               | XXS      | XXS      | XXS      | XXS      |
| ERP Class        | (Class G - A) | <b>B</b> | <b>B</b> | <b>B</b> | <b>B</b> |
| Tank capacity    | l             | 5        | 5        | 10       | 10       |
| Electrical power | W             | 2000     | 2000     | 2000     | 2000     |
| Heating time     | 20+55°C       | 10min    | 10min    | 19min    | 19min    |
| Empty weight     | Kg            | 4.5      | 4.5      | 6.5      | 6.5      |