



FREE STANDING WATER HEATERS						
CHARACTERISTICS						
Model	...	72280FWP	72281FZP	72282P	72289Z	72352(C)
Rated volume	L	150	200	300	500	1000
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,6
Rated voltage	V~	230	230	380-400 3N (230)	380-400 3N (230)	380-400 3N
Rated electrical power	kW	3	3	9 (3)	9 (3)	9 (12 (C))
Warm-up time from 12-75 °C	h	3.7	4.9	2.2 (6.6)	4.15 (12.45)	8.3 (6.2)
MIX 37 °C (temperature of the water in the water tank: 75 °C; water temperature of supply water: 12 °C)	L	378	500	680	1260	2520
Weight when empty	kg	35	42	54	103	204
CONNECTIONS						
1: Thermometer-manometer		HE	HE	ДА	ДА	ДА
7: Flange with heating element		-	-	-	-	-
9: Cold water inlet - Drain		G3/4 F	G3/4 F	G3/4 F	G1 F	G1 1/2 F
10: Circulation		G3/4 F	G3/4 F	G3/4 F	G3/4 F	G3/4 F
11: Hot water outlet		G3/4 F	G3/4 F	G3/4 F	G1 F	G1 1/2 F
DIMENSIONS						
A	mm	230	230	230	280	365
C	mm	680	720	860	1015	1050
D	mm	620	670	670	810	1210
P	mm	885	925	1305	1440	1725
G	mm	85	85	85	85	100
H	mm	1170	1230	1610	1760	2150
M	mm	710	760	760	900	1150

"C" - electrical power 12kW



Water heaters type:	storage water heaters
Installation:	floor standing
Capacity:	150, 200, 300, 500, 750, 1000, 1500 and, 2000 liters
Water tank:	enameled

Often, when it is necessary for a small capacity water heater to work intensively, its operating life is being shortened, so remember to choose a water heater capable to provide enough hot water for your needs. Define well the right capacity, based on the number of bathrooms and hot water consumers. We recommend the ELDOM Titan water heaters for family houses, office buildings and small production plants.

DESCRIPTION

- Economical – the thick insulation, made by a special formula guarantees minimal energy losses;
- Long life – high temperatures resistant water tank coating, due to the innovative enamel formula with increased content of zirconium (Zr);
- Safe – with five-level protection;
- Reliable anti-corrosion protection – two magnesium anodes system protects the entire water tank volume from the corrosive processes;
- External capillary thermostat;
- Anti-freeze protection;
- Capillary thermal cut out;
- Electrical tubular heating element – designed and manufactured by ELDOMINVEST using latest generation technology.
- The 300, 500, 750, 1000, 1500 and 2000 L models are equipped with an additional pressure regulator.

