



## C500: all simplicity

The **C500** central vacuum unit, simple and powerful:

- equipped with *two motors* and a *vacuum prevention valve*
- right and left dust inlet
- *Soft Start*
- air expulsion line directed upwards with *Ø63mm outlet diameter*.
- compatible with remote devices.



### Technical table for C500

Line		CM500C
Model		C500
Power supply	Volts	230
Motor power	Watts (W)	2.300
Motor	rpm	43.940
Turbine stages	no.	1
Socket power supply	Volts (V)	12
Vacuum power	Air Watts	1010
Air flow rate	m <sup>3</sup> /h	420
Max. vacuum	mbar	260
Noise level	dB	65
Filter cartridge surface area	cm <sup>2</sup>	12.000
Filter cartridge material	Material	POLYESTER
Container capacity	litres	23
Height	cm	106
Diameter	cm	32
Weight	kg	22
Compatibility with Dynamic Control display system code CMT800		YES (optional)
Compatibility with Remote panel kit		YES
Soft Start		YES
Right and left dust inlet		YES
Max no. of sockets (advised)	no.	29
Manufacturer's advised surface area	m <sup>2</sup>	800

### Components supplied



Bracket for central vacuum unit and anti-vibration devices



Sleeve and fasteners



12 V cable



230 V power supply cable

### Optional accessories



Code CM8890  
REMOTE panel kit With LED signals



Code CI365  
Plastic silencer ø63

