

**CPR**  
Unità Piatta/Ribassata  
Unit Slim/Reduced


**Taglia - Size**  
■ 122 ... 342

**Versione - Version**  
■ 1-2: Orizzontale - Horizontal  
■ 21-22: Verticale - Vertical

**Lato attacchi batteria - Coil connections side**  
■ **DX** = Destra - Right (STANDARD)  
■ **SX** = Sinistra - Left

Sigla per l'ordinazione  
Order identification code

**CPR 122 Z(\*) 1 DX = CPR 122-Z1-DX**



(\*) Cassa portante - Main casing

<b>Z</b>	<b>ZINCATO GALVANIZED</b>	Versioni in semplice pannello, autoportante, in lamiera zincata + isolamento termo-acustico interno Self-supporting single skin panel versions, made of galvanized steel + internal thermal-acoustic insulation
<b>P</b>	<b>PREVERNICIATO PRE-PAINTED</b>	Versioni in semplice pannello, autoportante, in lamiera preverniciata bianca RAL 9002 + isolamento termo-acustico interno Self-supporting single skin panel versions, made of white RAL 9002 pre-painted steel + internal thermal-acoustic insulation
<b>K</b>	<b>DOPPIO PANNELLO DOUBLE SKIN PANEL</b>	Versioni in Doppio pannello, autoportante, in lamiera zincata / Fibra vetro / Lamiera preverniciata bianca RAL 9002 Self-supporting double skin panel versions, made of Galvanized steel / Glass fibre / White RAL 9002 pre-painted steel

Taglia - Size	CPR	122	132	142	222	232	242	322	332	342
Pot. frigorifera Totale - Total Cooling cap.	W	6.010	7.480	8.590	10.300	12.900	15.000	13.600	17.200	20.200
Potenzialità Termica - Heating capacity	W	13.100	15.800	16.600	23.400	28.800	30.400	31.300	38.800	40.800
Portata aria - Air flow	m³/h	1.100	1.200	1.150	2.100	2.300	2.200	2.800	3.100	2.950
versioni-versions	<b>L</b> mm	800	800	800	1.200	1.200	1.200	1.600	1.600	1.600
<b>Z-P</b>	Peso netto - Net weight	Kg	34	35	37	48	50	53	63	65
versioni-versions	<b>L1</b> mm	840	840	840	1.240	1.240	1.240	1.640	1.640	1.640
<b>K</b>	Peso netto - Net weight	Kg	48	49	51	66	68	71	85	87